

In the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (currently amended) A wick for a dispenser for volatile liquid, comprising:
the dispenser includes a housing having an alignment member,
the wick comprises a first portion extending into a container holding the volatile liquid
and a second portion a body defining an opening, and in which wherein the opening is
adapted to receive the a alignment member associated with the housing dispenser.
2. (currently amended) The wick of claim 1, wherein the opening in the second portion of the
wick and the alignment member are substantially coaxially mounted is positioned in a top of the
wick.
3. (currently amended) The wick of claim 1, wherein the opening in the second portion of the
wick and the alignment member are substantially perpendicularly mounted is positioned in a side
of the wick.
4. (currently amended) The wick of claim 1, wherein a shape of the opening in the second
portion is formed has a shape is congruent with a shape of the alignment member.
5. (currently amended) The wick of claim 1, wherein a size of the opening in the second portion
of the wick is of a dimension larger than a size of the alignment member.
6. (currently amended) The wick of claim 1, wherein the housing of the dispenser includes a fan
and wherein the fan is aligned with the second portion of the wick in which the member is
affixed to the dispenser in which the body is aligned with the fan with the member received in
the opening .

7. (currently amended) The wick of claim 1 ~~2~~, wherein the body alignment member is elongated and wherein the opening in the second portion has a depth to accommodate the elongated alignment member ~~has a length in which the member engages the opening in a direction generally along the length of the body.~~

8. (currently amended) The wick of claim 1 ~~3~~, wherein the opening in the second portion of the wick extends along the side of the second portion body ~~is and wherein the alignment member is elongated and has a length in which the member engages the opening in a direction generally transverse to the length of the body.~~

9. (currently amended) The wick of claim 1, ~~wherein the housing comprises an including a housing defining another opening adapted to removably receive and retain a the container holding the volatile liquid and including the wick, through the other opening and into an interior of the housing in which and wherein the opening has a dimension width H [[:]] and in which the alignment member has a dimension width P, and wherein~~ in which P is less than H.

10. (canceled)

11. (currently amended) The wick of claim 9, wherein the alignment member is affixed to an interior surface of the housing, opposite the ~~other housing opening defined by the housing.~~

12. (canceled)

13. (canceled)

14. (currently amended) The wick of claim ~~11~~ 3, wherein the alignment member is affixed to an interior surface of the housing substantially perpendicular to the second portion of the wick extends in a direction generally transverse to a direction of insertion of the wick into the other opening of the housing.

15. (currently amended) The wick of claim 1, wherein ~~a perimeter of a cross-section of the alignment member taken generally transverse to a length of the member has a simple~~ has a geometric shape cross-section.

16. (currently amended) The wick of claim 1, wherein ~~[[,]]~~ the wick operates at ambient room temperature.

17. (new) A dispenser for dispensing volatile liquid with a wick, the dispenser comprising
a housing including a wick alignment member having a top end and a bottom end,
a container including volatile liquid,
the wick having two portions, the first portion extending into the container including
volatile liquid and the second portion extending away from the container, and wherein the second
portion comprises an opening adapted for receiving the wick receiving member.

18. (new) The dispenser of claim 17, wherein the housing further comprising a fan,
the fan being arranged in the housing such that the fan aligns with the second portion of
the wick.

19. (new) The dispenser of claim 18, wherein the container is removably mounted in the
housing.

20. (new) A wick for a dispenser for volatile liquid, comprising:
a container containing volatile liquid,
a wick having two portions, a first portion extending into the liquid in the reservoir and a
second portion extending outside the container, and
a housing holding the container securely,
the housing additionally comprising an alignment member which fits into an opening in
the second portion of the wick when the wick is correctly positioned for the dispensing of liquid.